



Printing date 06.04.2016 Version number 2 Revision: 06.04.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: ergo 3160 Paste
- -1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- Application of the substance / the mixture Silicate sealing
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

KISLING DEUTSCHLAND GmbH

Drillberg

D-97980 Bad Mergentheim

Telefon: +49-(0) 791-407 27-0 Telefax: +49-(0) 791-407 27-50

- Further information obtainable from: Safety Department
- Department issuing MSDS: ergo@kisling.com
- -1.4 Emergency telephone number: Tox Info Suisse: 145 / +41-44-2 51 51 51

SECTION 2: Hazards identification

- -2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

The product is not classified according to the CLP regulation.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008 Void
- Hazard pictograms Void
- Signal word Void
- Hazard statements Void
- Additional information:

EUH210 Safety data sheet available on request.

- 2.3 Other hazards
- Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures
- **Description:** Adhesive

| - Dangerous components: | | |
|--------------------------------|---|----------|
| | 2-propanone, 2,2',2"-[O,O',O"-(ethylsilylidyne)trioxime] | 0,1-<10% |
| Reg.nr.: 01-2119982962-22-xxxx | STOT RE 2, H373 | |
| CAS: 623-40-5 | 2-Pentanone oxime | 0,1-<10% |
| ELINCS: 484-470-6 | Acute Tox. 4, H302; Eye Irrit. 2, H319; Aquatic Chronic 3, H412 | |

- Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- -4.1 Description of first aid measures
- General information: Remove any clothing soiled by the product.
- After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

(Contd. on page 2)

Printing date 06.04.2016 Version number 2 Revision: 06.04.2016

Trade name: ergo 3160 Paste

(Contd. of page 1)

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: After contact with skin, wash with plenty of water.
- After eye contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

- After swallowing:

Rinse out mouth and then drink plenty of water.

If swallowed, do not induce vomiting: seek medical advice and show this container or label.

- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

- Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures

Particular danger of slipping on leaked/spilled product.

- 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

- 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 10 for information on "stability and reactivity".

See Section 13 for disposal information.

SECTION 7: Handling and storage

- -7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection:

No special precautions are necessary if used and stored according to specifications.

- -7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Protect from frost.

Protect from heat and direct sunlight.

- Maximum storage temperature: 30 °C
- Minimum storage temperature: 5 °C

(Contd. on page 3)

Printing date 06.04.2016 Version number 2 Revision: 06.04.2016

Trade name: ergo 3160 Paste

(Contd. of page 2)

-7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- -8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists valid during the making were used as basis.
- -8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- **Respiratory protection:** Use suitable respiratory protective device in case of insufficient ventilation.
- Protection of hands:

Protective gloves (EN 374)

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection: Goggles recommended during refilling

SECTION 9: Physical and chemical properties

| - 9.1 Information on basic physical a - General Information | nd chemical properties |
|--|------------------------|
| - Appearance: | |
| Form: | Pasty |
| Colour: | Grey |
| - Odour: | Characteristic |
| - Odour threshold: | Not determined. |
| - pH-value: | Not determined. |
| - Change in condition | |
| Melting point/Melting range: | Undetermined. |
| Boiling point/Boiling range: | Undetermined. |
| - Flash point: | Not applicable. |

(Contd. on page 4)

Printing date 06.04.2016 Version number 2 Revision: 06.04.2016

Trade name: ergo 3160 Paste

| | | (Contd. of page 3) |
|--|---|--------------------|
| - Flammability (solid, gaseous): | Not applicable. | |
| - Ignition temperature: | | |
| Decomposition temperature: | Not determined. | |
| - Self-igniting: | Product is not self-igniting. | |
| - Danger of explosion: | Product does not present an explosion hazard. | |
| - Explosion limits: | | |
| Lower: | Not determined. | |
| Upper: | Not determined. | |
| - Vapour pressure: | Not determined. | |
| - Density: | Not determined. | |
| - Relative density | Not determined. | |
| - Vapour density | Not determined. | |
| - Evaporation rate | Not determined. | |
| - Solubility in / Miscibility with | | |
| water: | Hydrolised. | |
| - Partition coefficient (n-octanol/wat | er): Not determined. | |
| - Viscosity: | | |
| Dynamic: | Not determined. | |
| Kinematic: | Not determined. | |
| - 9.2 Other information | No further relevant information available. | |

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

Protect from heat and direct sunlight.

- 10.3 Possibility of hazardous reactions

No dangerous reactions if used and stored according to specifications.

- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

No dangerous products of decomposition if used and stored according to specifications.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

| - LD/LC50 v | alues relevant for classification: |
|-------------|------------------------------------|
| 623-40-5 2- | Pentanone oxime |
| Oral LD50 | 1133 mg/kg (rat) |

- Primary irritant effect:
- Skin corrosion/irritation Repeated exposure may cause skin dryness or cracking.
- Serious eye damage/irritation Slight irritant effect possible.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Additional toxicological information:

No experimentally found toxicological data are available for this preparation.

(Contd. on page 5)

Printing date 06.04.2016 Version number 2 Revision: 06.04.2016

Trade name: ergo 3160 Paste

(Contd. of page 4)

- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- Additional ecological information:
- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Danger to drinking water if even small quantities leak into the ground.

Do not allow product to reach ground water, water course or undiluted sewage system.

- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- **Recommendation** Disposal must be made according to official regulations.
- Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

| SECTION 14: Transport informa | ation | |
|--|---------------------------|--|
| - 14.1 UN-Number - ADR, IMDG, IATA | Void | |
| - 14.2 UN proper shipping name - ADR, IMDG, IATA | Void | |
| - 14.3 Transport hazard class(es) | | |
| - ADR, ADN, IMDG, IATA - Class | Void | |
| - 14.4 Packing group - ADR, IMDG, IATA | Void | |
| - 14.5 Environmental hazards: | Not applicable. | |
| - 14.6 Special precautions for user | Not applicable. | |
| - 14.7 Transport in bulk according to Ann Marpol and the IBC Code | nex II of Not applicable. | |
| - UN "Model Regulation": | Void | |

DEGEN -

Printing date 06.04.2016 Version number 2 Revision: 06.04.2016

Trade name: ergo 3160 Paste

(Contd. of page 5)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- National regulations:
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases

H302 Harmful if swallowed.

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

SVHC: Substances of Very High Concern

Acute Tox. 4: Acute toxicity - Category 4

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

- * Data compared to the previous version altered.

DEGEN





Printing date 06.04.2016 Version number 2 Revision: 06.04.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: ergo 3160 Druckdose
- -1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- Application of the substance / the mixture Silicate sealing
- -1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

KISLING DEUTSCHLAND GmbH

Drillberg

D-97980 Bad Mergentheim

Telefon: +49-(0) 791-407 27-0 Telefax: +49-(0) 791-407 27-50

- Further information obtainable from: Safety Department
- Department issuing MSDS: ergo@kisling.com
- -1.4 Emergency telephone number: Tox Info Suisse: 145 / +41-44-2 51 51 51

SECTION 2: Hazards identification

- -2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms



GHS02

- Signal word Danger
- Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- -3.2 Mixtures
- Description: Active substance with propellant

| - Dangerous components: | | |
|--------------------------------|--|----------|
| CAS: 58190-57-1 | 2-propanone, 2,2',2"-[O,O',O"-(ethylsilylidyne)trioxime] | 0,1-<10% |
| Reg.nr.: 01-2119982962-22-xxxx | STOT RE 2, H373 | |

(Contd. on page 2)

Printing date 06.04.2016 Version number 2 Revision: 06.04.2016

Trade name: ergo 3160 Druckdose

| CAS: 623-40-5 ELINCS: 484-470-6 | 2-Pentanone oxime Acute Tox. 4, H302; Eye Irrit. 2, H319; Aquatic Chronic 3, H412 | ontd. of page 1) 0,1-<10% |
|--|---|---------------------------|
| | In the propellant-mixture: | |
| CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 | propane Flam. Gas 1, H220; Press. Gas C, H280 | _ |
| CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 | butane Flam. Gas 1, H220; Press. Gas C, H280 | |

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information: Remove any clothing soiled by the product.
- After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- Additional information: For the wording of the listed hazard phrases refer to section 16.

- After skin contact: After contact with skin, wash with plenty of water.
- After eye contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

- After swallowing:

Rinse out mouth and then drink plenty of water.

If swallowed, do not induce vomiting: seek medical advice and show this container or label.

- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- -5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

- Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

Ensure adequate ventilation

(Contd. on page 3)

Printing date 06.04.2016 Version number 2 Revision: 06.04.2016

Trade name: ergo 3160 Druckdose

(Contd. of page 2)

- 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow product to reach sewage system or any water course.

- 6.3 Methods and material for containment and cleaning up:

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

Ensure adequate ventilation.

- 6.4 Reference to other sections

Fumes can combine with air to form an explosive mixture.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 10 for information on "stability and reactivity".

See Section 13 for disposal information.

SECTION 7: Handling and storage

-7.1 Precautions for safe handling

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

- Information about fire - and explosion protection:

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

-7.2 Conditions for safe storage, including any incompatibilities

- Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Protect from heat and direct sunlight.

Store under lock and key and out of the reach of children.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

- Maximum storage temperature: 30 °C
- Minimum storage temperature: 5 °C
- -7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- -8.1 Control parameters

| - Ingredients with | - Ingredients with limit values that require monitoring at the workplace: | | |
|--------------------|---|--|--|
| 74-98-6 propane | | | |
| AGW (Germany) | Long-term value: 1800 mg/m³, 1000 ppm 4(II);DFG | | |
| 106-97-8 butane | | | |
| AGW (Germany) | Long-term value: 2400 mg/m³, 1000 ppm 4(II);DFG | | |

- Additional information:

If used according to specifications the propellant (contains propane/butane) is not liberated.

The lists valid during the making were used as basis.

- 8.2 Exposure controls

- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

(Contd. on page 4)

Printing date 06.04.2016 Version number 2 Revision: 06.04.2016

Trade name: ergo 3160 Druckdose

(Contd. of page 3)

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- Respiratory protection: Not required.

- Protection of hands:

Protective gloves on prolonged contact with skin.

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection: Avoid contact with the eyes.

SECTION 9: Physical and chemical properties

| 520116117. I hysical and elemical properties | |
|--|--|
| - 9.1 Information on basic physical ar | nd chemical properties |
| - General Information | |
| - Appearance: | |
| Form: | Pasty |
| Colour: | Grey |
| - Odour: | Characteristic |
| - Odour threshold: | Not determined. |
| - pH-value: | Not determined. |
| - Change in condition | |
| Melting point/Melting range: | Not applicable, as aerosol. |
| Boiling point/Boiling range: | Not applicable, as aerosol. |
| - Flash point: | Not applicable, as aerosol. |
| - Flammability (solid, gaseous): | Not applicable. |
| - Ignition temperature: | |
| Decomposition temperature: | Not determined. |
| - Self-igniting: | Product is not self-igniting. |
| - Danger of explosion: | Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. |
| | Buildup of explosive mixtures possible without sufficient ventilation. |
| - Explosion limits: | |
| Lower: | Not determined. |
| Upper: | Not determined. |
| - Vapour pressure: | Not determined. |
| - Density: | Not determined. |

(Contd. on page 5)

Printing date 06.04.2016 Version number 2 Revision: 06.04.2016

Trade name: ergo 3160 Druckdose

(Contd. of page 4)

| - Relative density | Not determined. |
|--------------------|-----------------|
| - Vapour density | Not determined. |
| - Evaporation rate | Not applicable. |

- Solubility in / Miscibility with

water: Hydrolised.

- Partition coefficient (n-octanol/water): Not determined.

- Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

- **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: Protect from heat and direct sunlight.
- 10.3 Possibility of hazardous reactions Danger of bursting.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

No dangerous products of decomposition if used and stored according to specifications.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

| - LD/LC5 | - LD/LC50 values relevant for classification: | | |
|-----------|---|------------------|--|
| 623-40-5 | 2-Pentano | ne oxime | |
| Oral | LD50 | 1133 mg/kg (rat) | |
| 106-97-8 | butane | | |
| Inhalativ | e LC50/4 h | 658 mg/l (rat) | |

- Primary irritant effect:
- Skin corrosion/irritation Repeated exposure may cause skin dryness or cracking.
- Serious eye damage/irritation Slight irritant effect possible.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Additional toxicological information:

No experimentally found toxicological data are available for this preparation.

- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.

(Contd. on page 6)

Printing date 06.04.2016 Version number 2 Revision: 06.04.2016

Trade name: ergo 3160 Druckdose

(Contd. of page 5)

- Additional ecological information:
- General notes:

Water hazard class (German Regulation) is valid for the active agent.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Danger to drinking water if even small quantities leak into the ground.

Do not allow product to reach ground water, water course or undiluted sewage system.

- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation Disposal must be made according to official regulations.
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information - 14.1 UN-Number - ADR, IMDG, IATA UN1950 - 14.2 UN proper shipping name 1950 AEROSOLS - ADR - IMDG **AEROSOLS** - IATA Aerosols, flammable - 14.3 Transport hazard class(es) - ADR 2 5F Gases. - Class - Label 2.1 - IMDG - Class 2 Gases. - Label 2.1 - IATA - Class 2.1 - Label 2.1 - 14.4 Packing group - ADR, IMDG, IATA Void (Contd. on page 7)

Printing date 06.04.2016 Version number 2 Revision: 06.04.2016

Trade name: ergo 3160 Druckdose

| | (Contd. of page |
|---|--|
| - 14.5 Environmental hazards: | Not applicable. |
| - 14.6 Special precautions for user | Warning: Gases. |
| - Danger code (Kemler): | - |
| - EMS Number: | F-D,S-U |
| - Stowage Code | SW1 Protected from sources of heat. |
| | SW22 For AEROSOLS with a maximum capacity of |
| | litre: Category A. For AEROSOLS with a capacity above |
| | 1 litre: Category B. For WASTE AEROSOLS: Categor |
| g 4 G 1 | C, Clear of living quarters. |
| - Segregation Code | SG69 For AEROSOLS with a maximum capacity of |
| | litre: Segregation as for class 9. Stow "separated from class 1 except for division 1.4. For AEROSOLS with |
| | capacity above 1 litre: Segregation as for the appropria |
| | subdivision of class 2. For WASTE AEROSOLS |
| | Segregation as for the appropriate subdivision of class 2. |
| 14.7 Tuonanantin kulli aasandina ta Aus | |
| 14.7 Transport in bulk according to Ann Marpol and the IBC Code | Not applicable. |
| | Tvot applicable. |
| - Transport/Additional information: | |
| - ADR | |
| - Limited quantities (LQ) | 1L |
| - Excepted quantities (EQ) | Code: E0 |
| | Not permitted as Excepted Quantity |
| - Transport category | 2 |
| - Tunnel restriction code | D |
| - IMDG | |
| - Limited quantities (LQ) | 1L |
| - Excepted quantities (EQ) | Code: E0 |
| | Not permitted as Excepted Quantity |
| | 1 |

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- National regulations:
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 8)

(Contd. of page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.04.2016 Version number 2 Revision: 06.04.2016

Trade name: ergo 3160 Druckdose

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

SVHC: Substances of Very High Concern Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas C: Gases under pressure – Compressed gas

Acute Tox. 4: Acute toxicity - Category 4

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

- * Data compared to the previous version altered.

DEGEN