



Kisling AG

**Motorenstrasse 102
CH-8620 Wetzikon**

Telefon +41 (0)58 272 01 01
Telefax +41 (0)58 272 01 03

info@kisling.com
www.kisling.com

Technical Data Sheet

ergo.® 9153 Adhesive-Remover

General Description

ergo.® 9153 Adhesive Remover is based on different organic solvents with high boiling point. After application, the evaporation of the remover is slow. Therefore, it can react with the adhesive for longer times and dissolve or swell the cured adhesive.

Remaining liquid adhesive material can be removed, too.

Instructions

Apply the adhesive remover on the cured adhesives or immerse parts into the liquid. The adhesive remover will dissolve the adhesive or will swell the adhesive in such a way that mechanical removal is easy. The time necessary to react with the adhesive is depending on temperature and other factors like volume of the cured adhesive or the geometry of the parts. We recommend to evaluate this in tests.

Caution: Please check compatibility of plastic substrates with the adhesive remover prior to usage. Please also prevent static charging of the parts and take care of well ventilation (e.g. working in a fume-hood, etc.)

Physical Properties

Chemical Base	organic solvents
Colour	colorless to slightly yellow
Density at 20°C	1,00 – 1,10 g/cm ³
Viscosity at 25°C	< 10 mPas
Flash-Point	> 90 °C DIN 55213
Shelf-Life at 23°C	2 years

Packaging

1 Liter bottle or can, other packaging possible on request

WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that KISLING products are safe, effective, and fully satisfactory for the intended end use. KISLING sole warranty is that the product will meet the KISLING sales specifications in effect at the time of shipment. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted. KISLING specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability. Unless KISLING provides you with a specific, duly signed endorsement of fitness for use, KISLING disclaims liability for any incidental or consequential damages. Suggestions of uses should not be taken as inducements to infringe any particular patent.