

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.01.2015

Version number 1

Revision: 20.01.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier

- Trade name: ergo 9195 Aerosol

- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- Application of the substance / the mixture CA-Cleaner

- 1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier:

Kisling AG

Motorenstrasse 102

CH-8620 Wetzikon

Telefon: +41-(0) 58-272 0 272

Telefax: +41-(0) 58-272 0 273

- Further information obtainable from: Safety Department

- Department issuing MSDS: ergo@kisling.com

- 1.4 Emergency telephone number: Swiss Toxicological Information Centre: +41-(0) 44-2 51 51 51

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture

- Classification according to Regulation (EC) No 1272/2008

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Xi; Irritant

R36: Irritating to eyes.

F+; Extremely flammable

R12: Extremely flammable.

R67: Vapours may cause drowsiness and dizziness.

- Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurised container.

Has a narcotising effect.

- Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms



GHS02 GHS07

- Signal word Danger

- Hazard-determining components of labelling:

propan-2-ol

(Contd. on page 2)

CHGEN

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.01.2015

Version number 1

Revision: 20.01.2015

Trade name: ergo 9195 Aerosol

(Contd. of page 1)

- Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P261 Avoid breathing mist/vapours/spray.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Additional information:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Buildup of explosive mixtures possible without sufficient ventilation.

- 2.3 Other hazards**- Results of PBT and vPvB assessment****- PBT:** Not applicable.**- vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****- 3.2 Mixtures****- Description:** Active substance with propellant**- Dangerous components:**

CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol Xi R36; F R11 R67 Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	25-<100%
CAS: 124-38-9 EINECS: 204-696-9	carbon dioxide Press. Gas L, H280	3-<10%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0	butane F+ R12 Flam. Gas 1, H220; Press. Gas C, H280	1-<3%

- Regulation (EC) No 648/2004 on detergents:

aliphatic hydrocarbons

< 5%

- Additional information: For the wording of the listed risk phrases refer to section 16.**SECTION 4: First aid measures****- 4.1 Description of first aid measures****- General information:** Remove any clothing soiled by the product.**- After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: After contact with skin, wash with plenty of water.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.01.2015

Version number 1

Revision: 20.01.2015

Trade name: ergo 9195 Aerosol

(Contd. of page 2)

- **After eye contact:**
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- **After swallowing:**
Rinse out mouth and then drink plenty of water.
If swallowed, do not induce vomiting: seek medical advice and show this container or label.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
Can form explosive gas-air mixtures.
Formation of toxic gases is possible during heating or in case of fire.
In case of fire, the following can be released:
Carbon monoxide and carbon dioxide
Danger of forming toxic pyrolysis products.
Under certain fire conditions, traces of other toxic gases cannot be excluded.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.
- **Additional information**
Cool endangered receptacles with water spray.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources.
Avoid contact with the eyes and skin.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
- **6.3 Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Absorb liquid components with liquid-binding material.
Dispose of the material collected according to regulations.
- **6.4 Reference to other sections**
Fumes can combine with air to form an explosive mixture.
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 10 for information on "stability and reactivity".
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

CHGEN

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.01.2015

Version number 1

Revision: 20.01.2015

Trade name: ergo 9195 Aerosol

(Contd. of page 3)

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

- Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

Buildup of explosive mixtures possible without sufficient ventilation.

- 7.2 Conditions for safe storage, including any incompatibilities

- Storage:

- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- Information about storage in one common storage facility: Not required.

- Further information about storage conditions:

Protect from heat and direct sunlight.

Store under lock and key and out of the reach of children.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.

- 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:

67-63-0 propan-2-ol

MAK (Switzerland)	Short-term value: 1000 mg/m ³ , 400 ppm Long-term value: 500 mg/m ³ , 200 ppm B SSc;
-------------------	------------------------------------------------------------------------------------------------------------------

124-38-9 carbon dioxide

MAK (Switzerland)	Long-term value: 9000 mg/m ³ , 5000 ppm
-------------------	----------------------------------------------------

106-97-8 butane

MAK (Switzerland)	Short-term value: 7200 mg/m ³ , 3200 ppm Long-term value: 1900 mg/m ³ , 800 ppm
-------------------	----------------------------------------------------------------------------------------------------------

- DNELs

67-63-0 propan-2-ol

Oral	Langzeit, Systemische Effekte	26 mg/kg bw/day (all)
Dermal	Langzeit, Systemische Effekte	319 mg/kg bw/day (all) 888 mg/kg bw/day (ber)
Inhalative	Langzeit, Systemische Effekte	89 mg/m ³ (all) 500 mg/m ³ (ber)

- PNECs

67-63-0 propan-2-ol

PNEC Boden	28 mg/kg Boden (-)
PNEC Kläranlage	2251 mg/l (-)
PNEC Meerwasser	140,9 mg/l (-)
PNEC Meerwassersediment	552 mg/kg Sediment (-)
PNEC Süßwasser	140,9 mg/l (-)
PNEC Süßwassersediment	552 mg/kg Sediment (-)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.01.2015

Version number 1

Revision: 20.01.2015

Trade name: ergo 9195 Aerosol

(Contd. of page 4)

- Ingredients with biological limit values:**67-63-0 propan-2-ol**

BAT (Switzerland)	25 mg/l Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende Biol. Parameter: Aceton
	25 mg/l Untersuchungsmaterial: Vollblut Probennahmezeitpunkt: Expositionsende bzw. Schichtende Biol. Parameter: Aceton

- Additional information: The lists valid during the making were used as basis.

- 8.2 Exposure controls**- Personal protective equipment:****- General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Filter AX

- Protection of hands:

Protective gloves (EN 374)

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection: Safety glasses

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties**- General Information****- Appearance:**

Form: Aerosol

Colour: Clear

- Odour: Alcohol-like

- Odour threshold: Not determined.

- pH-value: Not determined.

- Change in condition

Melting point/Melting range: Not applicable, as aerosol.

(Contd. on page 6)

CHGEN

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.01.2015

Version number 1

Revision: 20.01.2015

Trade name: ergo 9195 Aerosol

(Contd. of page 5)

Boiling point/Boiling range:	Not applicable, as aerosol.
- Flash point:	Not applicable, as aerosol.
- Flammability (solid, gaseous):	Not applicable.
- Ignition temperature:	
Decomposition temperature:	Not determined.
- Self-igniting:	Product is not self-igniting.
- Danger of explosion:	Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Buildup of explosive mixtures possible without sufficient ventilation.
- Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
- Vapour pressure:	Not determined.
- Density at 20 °C:	0,74 g/cm ³
- Relative density	Not determined.
- Vapour density	Not determined.
- Evaporation rate	Not applicable.
- Solubility in / Miscibility with water:	Fully miscible.
- Partition coefficient (n-octanol/water):	Not determined.
- Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
- 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity
- 10.2 Chemical stability
- **Thermal decomposition / conditions to be avoided:** Protect from heat and direct sunlight.
- **10.3 Possibility of hazardous reactions**
Danger of bursting.
Forms explosive gas mixture with air.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
No dangerous products of decomposition if used and stored according to specifications.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- **Acute toxicity:**

- LD/LC50 values relevant for classification:		
67-63-0 propan-2-ol		
Oral	LD50	4570 mg/kg (rat)
Dermal	LD50	13400 mg/kg (rab)

(Contd. on page 7)

CHGEN

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.01.2015

Version number 1

Revision: 20.01.2015

Trade name: ergo 9195 Aerosol

(Contd. of page 6)

Inhalative	LC50/4 h	30 mg/l (rat)
106-97-8 butane		
Inhalative	LC50/4 h	658 mg/l (rat)

- Primary irritant effect:
- on the skin: Repeated exposure may cause skin dryness or cracking.

- on the eye: Causes serious eye irritation.

- Sensitisation: No sensitising effects known.

- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

Vapours have narcotic effect.

No experimentally found toxicological data are available for this preparation.

SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity:

67-63-0 propan-2-ol		
EC50/72 h	>	1000 mg/l (Algae)

- 12.2 Persistence and degradability No further relevant information available.

- 12.3 Bioaccumulative potential No further relevant information available.

- 12.4 Mobility in soil No further relevant information available.

- Additional ecological information:
- General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Water hazard class (German Regulation) is valid for the active agent.

- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.

- vPvB: Not applicable.

- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation Disposal must be made according to official regulations.

- European waste catalogue	
16 00 00	WASTES NOT OTHERWISE SPECIFIED IN THE LIST
16 05 00	gases in pressure containers and discarded chemicals
16 05 04*	gases in pressure containers (including halons) containing dangerous substances

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- 14.1 UN-Number	
- ADR, IMDG, IATA	UN1950
- 14.2 UN proper shipping name	
- ADR	1950 AEROSOLS

(Contd. on page 8)

CHGEN

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.01.2015

Version number 1

Revision: 20.01.2015

Trade name: ergo 9195 Aerosol

(Contd. of page 7)

- IMDG	AEROSOLS
- IATA	AEROSOLS, flammable

- 14.3 Transport hazard class(es)

- ADR



- Class	2 5F Gases.
- Label	2.1

- IMDG



- Class	2 Gases.
- Label	2.1

- IATA



- Class	2.1
- Label	2.1

- 14.4 Packing group

- ADR, IMDG, IATA Void

- 14.5 Environmental hazards: Not applicable.

- 14.6 Special precautions for user Warning: Gases.

- EMS Number: F-D,S-U

- 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

- Transport/Additional information:

- ADR

- Limited quantities (LQ)	1L
- Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
- Transport category	2
- Tunnel restriction code	D

- IMDG

- Limited quantities (LQ)	1L
- Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity

- UN "Model Regulation": UN1950, AEROSOLS, 2.1

CHGEN

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.01.2015

Version number 1

Revision: 20.01.2015

Trade name: ergo 9195 Aerosol

(Contd. of page 8)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- National regulations:

- Waterhazard class:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

Water hazard class (German Regulation) is valid for the active agent.

- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

R11 Highly flammable.

R12 Extremely flammable.

R36 Irritating to eyes.

R67 Vapours may cause drowsiness and dizziness.

- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Gas 1: Flammable gases, Hazard Category 1

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas C: Gases under pressure: Compressed gas

Press. Gas L: Gases under pressure: Liquefied gas

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

CHGEN